

TUMBLE DRYERS

DESIGNED TO MEET ALL NEEDS

Features

DS-45-60-80 STANDARD

- Construction in grey skinplate, stainless steel look.
- Big loading door (opening of 180°).
- Transmission by pulley and belt, with inverter.
- Front subjection by 2 strong and high-resistant wheels.
- **Timer Range:** Analogic control with time and temperature selection. Light indication of heating. (These models do not allow the moisture control option).
- **PM Electronic Control Range:** Electronic control. Easy and intuitive to use, the electronic control offers a complete control of the process.
- Inverter: All models offer the reverse turning of the drum.
- Stainless Steel Drum as standard.
- Mixed axial-radial airflow to optimise and maximise the airflow circuit in the drum.
- Efficient Drum: The new drum with stamped holes makes sure the linen is gently handled.
- Cool Down: Anti-wrinkle at the end of cycle.
- Models available in electric, gas or steam heating.



DS-45-60-80 PM

DS-45-60-80



Emissions CO2/carbon footprint



Energy efficiency



Stainless steel



Microprocessor



Variator: improves inverter performance



Efficient drum design



Dual airflow



Easy maintenance



Filter

Options

- Smart Dry: Intelligent Moisture Control.
- Fire Off: Integrated Fire Extinguishing System.
- Double doorglass.
- Stainless steel body.
- Stainless steel front panel.
- Low pressure steam battery.
- Model versions in 60 Hz.
- Marine versions 440V III 50/60 Hz No neutral or 480V III 50/60 Hz No neutral.