

CTP-260-330/100

FLATWORK IRONERS FOR BIG PRODUCTIONS

FEATURES:

- Flatwork ironers, with front feed and return.
- Roll sizes: 2.600 and 3.300 mm long and diameter 1.000 mm.
- Panels in painted steel.
- **One or two working lanes:** one lane for bedsheets and two lanes for tablecloth and smaller pieces.
- **Length fold** (1 or 2 folds) and **crossfold** (up to 3 folds).
- Folding system by photocells and compressed air.
- Two types of linen stacker, with possibility to program the number of items stacked. The stacker can be positioned on either side of the machine.
- Polished steel roll, with finger guard.
- CE certificate and gas certifications.
- Frequency control.
- Feeding and ironing belts are Nomex.
- Touch-screen control: programs can be created with speed control (between 3 and 18 mts/min), temperature and folding parameters.
- Big output capacity, depending on the residual moisture of the linen, up to 290 kg/hour directly from the high spin washer extractor.
- Powerful exhaust system.
- Electric, gas or steam heating.
- **NEW** gas model with **standard radiant burner. 25% gas consumption savings and 25% more production.**



Touch technology



Microprocessor



Inverter



Chromed roll



Easy maintenance



Drying



Ironing



Length fold



Cross fold



Stacking

OPTIONS:

- Automatic 1 lane clamp feeder with vacuum feeding belts.
- Small pieces back collector: 2 or 4 lanes + By-Pass.
- Vacuum feeding belts.
- Partial by pass, so different programs can be used in each of the 2 working lanes.
- Linen reject system.
- Double air pressure in length folds for thicker linen.
- Stacker - 1 or 2 lanes.
- Compact (roll-off) stacker - only in 1 lane models.
- Special voltage.